

LH4CD (A.B.)

4-ЗУБАЯ КОНЦЕВАЯ ФРЕЗА
С ПЛОСКИМ ТОРЦОМ ДЛЯ ЧЕРНОВОЙ ОБРАБОТКИ

Угол наклона
винтовой
канавки



Код	Диаметр режущей части (d ₁)	Длина режущей части (l ₂)	Общая длина (l ₁)	Диаметр хвостовика (d ₂)
LH4CDA-060	6,0	15	50	6
LH4CDA-080	8,0	20	60	8
LH4CDA-100	10,0	25	75	10
LH4CDA-120	12,0	30	75	12
LH4CDA-160	16,0	40	100	16
LH4CDA-200	20,0	40	100	20
LH4CDB-060	6,0	15	100	6
LH4CDB-080	8,0	20	100	8
LH4CDB-100	10,0	25	100	10
LH4CDB-120	12,0	30	100	12

A60

общее назначение

LH 250	MG	0.6 μm	CO 10%	HRC > 50	TiAlN
--------	----	-----------	-----------	-------------	-------

LH 460	MG	0.6 μm	CO 10%	HRC > 55	AlTiN
--------	----	-----------	-----------	-------------	-------

высокоскоростная
обработка

LH 500	UMG	0.5 μm	CO 12%	HRC > 60	AlTiN
--------	-----	-----------	-----------	-------------	-------

