

LH4EM (A.B.C.)

4-ЗУБАЯ КОНЦЕВАЯ ФРЕЗА
С УДЛИНЕННОЙ РАБОЧЕЙ ЧАСТЬЮ

Угол наклона
винтовой
канавки



Код	Диаметр режущей части (d ₁)	Длина режущей части (l ₂)	Общая длина (l ₁)	Диаметр хвостовика (d ₂)
LH3EMA-010	1,0	5	75	4
LH3EMA-015	1,5	6	75	4
LH3EMA-020	2,0	9	75	4
LH3EMA-025	2,5	10	75	4
LH3EMA-030	3,0	15	75	4
LH3EMA-035	3,5	15	75	4
LH3EMA-040	4,0	20	75	4
LH3EMA-045	4,5	20	75	6
LH3EMA-050	5,0	25	75	6
LH3EMA-055	5,5	25	75	6
LH3EMA-060	6,0	25	75	6
LH3EMA-065	6,5	25	75	8
LH3EMA-070	7,0	25	75	8
LH3EMA-075	7,5	25	75	8
LH3EMA-080	8,0	30	75	8
LH3EMB-030	3,0	15	100	6
LH3EMB-040	4,0	25	100	6
LH3EMB-050	5,0	30	100	6
LH3EMB-060	6,0	30	100	6
LH3EMB-070	7,0	35	100	8
LH3EMB-080	8,0	35	100	8
LH3EMB-090	9,0	40	100	10
LH3EMB-100	10,0	40	100	10
LH3EMB-110	11,0	45	100	12
LH3EMB-120	12,0	45	100	12
LH3EMC-080	8,0	40	150	8
LH3EMC-100	10,0	50	150	10
LH3EMC-120	12,0	50	150	12
LH3EMC-160	16,0	70	150	16
LH3EMC-180	18,0	80	150	20
LH3EMC-200	20,0	80	150	20

A16

общее назначение

LH 250 MG 0.6 μm CO 10% HRC > 50 TiAlN

LH 460 MG 0.6 μm CO 10% HRC > 55 AlTiN

высокоскоростная обработка

LH 500 UMG 0.5 μm CO 12% HRC > 60 AlTiN

LH 550 UMG 0.2 μm CO 9% HRC > 65-68 AlTiN

