



# Boring Bars 內孔車刀

C-SDUC  
E-SDUC  
S-SDUC  
93°



C-Carbide Shank 鎢鋼柄  
S-Steel Shank 鋼柄  
E-Carbide Shank with Coolant 附油孔鎢鋼柄

Order No.	Insert	Dimensions					Parts	Wrench
Right / Left		D	F	L	B	K°		
C10M-SDUCR07	DCMT0702	10	7	150	13	10°	CS25060	FT-7
C12Q-SDUCR07	DCMT0702	12	9	180	16	8°	CS25060	FT-7
C16R-SDUCR07	DCMT0702	16	11	200	20	6°	CS25060	FT-7
C16R-SDUCR11	DCMT11T3	16	11	200	20	7°	CS35095	FT-15
C20S-SDUCR11	DCMT11T3	20	13	250	25	8°	CS35095	FT-15
C25T-SDUCR11	DCMT11T3	25	17	300	32	4°	CS35095	FT-15
E10Q-SDUCR07	DCMT0702	10	7	180	13	10°	CS25060	FT-7
E12R-SDUCR07	DCMT0702	12	9	200	16	8°	CS25060	FT-7
E16R-SDUCR07	DCMT0702	16	11	200	20	6°	CS25060	FT-7
E20S-SDUCR11	DCMT11T3	20	13	250	25	8°	CS35095	FT-15
E25T-SDUCR11	DCMT11T3	25	17	300	32	4V	CS35095	FT-15
S10M-SDUCR/L07	DCMT0702	10	7	150	13	10°	CS25060	FT-7
S12M-SDUCR/L07	DCMT0702	12	9	150	16	8°	CS25060	FT-7
S16Q-SDUCR/L07	DCMT0702	16	11	180	20	6°	CS25060	FT-7
S20R-SDUCR/L07	DCMT0702	20	13	200	25	5°	CS25060	FT-7
S16Q-SDUCR/L11	DCMT11T3	16	11	180	20	7°	CS35095	FT-15
S20R-SDUCR/L11	DCMT11T3	20	13	200	25	8°	CS35095	FT-15
S25R-SDUCR/L11	DCMT11T3	25	17	200	32	4°	CS35095	FT-15
S32S-SDUCR/L11	DCMT11T3	32	22	250	39	4°	CS35095	FT-15
S40T-SDUCR/L11	DCMT11T3	40	24	300	50	2°	CS35095	FT-15